



# L122XXX

## Synthetic Rope Horizontal Lifeline System

### FEATURES

- Engineered handle on the Tension-Indicating Ratchet bends when the system is properly tensioned
- In-line energy absorber is designed to limit the maximum arrest load to less than 2,500 pounds on the end anchorages
- 10,000 pound minimum breaking strength  $\frac{5}{8}$  inch static kernmantle rope
- High strength polyester back pack with a reinforced bottom for easy transport
- Snap hooks are self-locking with a minimum tensile break strength of 5,000 pounds, and a 3,600 pound gate rating



### SPECIFICATIONS

| Model No. | Lifeline Length    | Anchorage Connector         | Tensioner                     | Max Number of Users | Capacity per User   | Approx. Weight      | Compliance Standards              |
|-----------|--------------------|-----------------------------|-------------------------------|---------------------|---------------------|---------------------|-----------------------------------|
| L122030   | 30 ft<br>(457 mm)  | A320001-WB<br>D-Bolt Anchor | Tension-Indicating<br>Ratchet | 2                   | 400 lbs<br>(181 kg) | 32 lbs<br>(14.5 kg) | OSHA 29 CFR<br>1910.66 & 1926.502 |
| L122060   | 60 ft<br>(457 mm)  | A320001-WB<br>D-Bolt Anchor | Tension-Indicating<br>Ratchet | 2                   | 400 lbs<br>(181 kg) | 33 lbs<br>(15.0 kg) | OSHA 29 CFR<br>1910.66 & 1926.502 |
| L122100   | 100 ft<br>(457 mm) | A320001-WB<br>D-Bolt Anchor | Tension-Indicating<br>Ratchet | 2                   | 400 lbs<br>(181 kg) | 37 lbs<br>(16.8 kg) | OSHA 29 CFR<br>1910.66 & 1926.502 |

**⚠ WARNING:** Compliant fall protection equipment must only be used as it was designed. Users MUST read and understand all user instructions provided with the product. Before using a fall arrest system, users must be trained in the safe use of the system, as required by OSHA 29 CFR 1910.30 and 1926.503, or local safety regulations. Misuse or failure to follow these warnings and instructions may result in injury or even death.

WORK SAFE! WORK SMART!

## Technical Data Sheet

WERNER CO. CORPORATE HEADQUARTERS: 93 Werner Rd., Greenville, PA 16125-9499

TEL: 888-523-3370 FAX: (724) 588-0315 [www.wernerco.com](http://www.wernerco.com)