



ROLAIR® STANDARD FEATURES

- PUMP:** ROLAIR® Quality, Single Stage, Ball Bearings, Cast-Iron Cylinder, Stainless-Steel Reed Valves and Splash Lubrication Ensure Longer Life.
- MOTOR:** 2 HP, 3400 RPM, S-1 Rated for Continuous Duty, Low-Amp Draw, Overload Protection with Manual Reset, 115 Volt, 60 Hz, Heavy-Duty/Industrial-Grade with Ball Bearings for Greater Durability.

SPECIFICATIONS

MODEL	MOTOR HP	# OF CYLS.	CU. FT. DISPLACED	CU. FT. DELIVERED @ 90 PSI	TANK CAP. (GAL.)	DIMENSIONS (L X W X H) (INCHES)	APPROX. SHIPPING WT. (LB.)
FC2002HBP6	2	1	8.7	4.1	5.3	16 x 14 x 31	63

STANDARD EQUIPMENT

- Start/Stop Pressure Switch with On/Off Lever
- Air Line Regulator and Pressure Gauge
- Dolly-Cart with Wheels for Easy Maneuvering
- Tank Pressure Gauge
- Safety Relief Valve
- Intake Filter Silencer
- 14.2 Amp Motor
- Initial 12 oz. Oil Fill Included