

# **PREMIUM SUBMERSIBLE STAINLESS STEEL SUMP PUMPS**

### **APPLICATIONS**

Ideal for high-volume water removal in residential spaces such as basements and crawl spaces.

### **FEATURES & BENEFITS**

- Automatic submersible stainless steel sump pump ideal for aggressive water applications
- Heavy-duty stainless steel and cast iron construction for years of service and reliability
- Clog-resistant design is capable of passing 3/4" diameter semi-solids
- · Piggyback float switch for reliable automatic operation



RL-SS50T

RL-SS50V

Model	ltem No.	UPC	HP	Volts	Switch	Discharge	Amps	Cord		Gallons Per Hour at Height				Shut-	On/Off	Min. Basin	
								Length	0′	5′	10′	15′	20′	30′	Off	Levels	Diameter
RL-SS50V	14942780	0 10121 14436 1				1-1/2" FNPT		10′		3000	2400	1800	-	-	25'	On: 7.5" Off: 4.5"	11" or more
RL-SS50T	14942781	0 10121 14437 8	1/2	115	Tethered	1-1/2" FNPT	5	10′	3450	3000	2400	1800	-	-	25'	On: 13.8"-14.8" Off: 5.5"-6.5"	18" or more
RL-SS100T	14942782	0 10121 14438 5	1	115	Tethered	2" FNPT 1-1/2" FNPT adapter incl	8	20'	5300	4800	4300	3700	3000	1300	35'	On: 15"–18" Off: 7"–10"	18" or more

## **CARTON SPECIFICATIONS**

Model	Length	Width	Height	Weight (lbs)	Carton Cubes (cu ft)	Pallet Quantity	Quantity per Layer	Layers per Pallet
RL-SS50V	7.12"	10″	17"	22.5	0.70	40	20	2
RL-SS50T	7"	10.5"	17"	22.5	0.72	40	20	2
RL-SS100T	10″	11″	18″	33.6	1.15	32	16	2

#### 40 35 30 25 Total Dynamic Head (ft) RL-SS100T 20 RL-SS50T and RL-SS50V 15 10 5 0 1000 2000 3000 4000 5000 6000 0 Capacity - US gph

#### Premium Submersible Stainless Steel Sump Pumps

#### 🗖 MENU