

MATERIAL SAFETY DATA SHEET

Mi-T-M Corp.
8650 Enterprise Drive
Peosta, IA 52068
Ph: 800-367-6486

Hazard Rankings -* NFPA
Health Hazard 1
Flammability 0
Reactivity 0
*See bottom of page

Product Name: **Mi-T-M CONCENTRATED DECK & HOUSE WASH** Emergency Phone #1-800-535-5053

1. IDENTIFICATION

CHEMICAL NAME AND SYNONYMS:

Not applicable

CHEMICAL

FAMILY: Alkaline Cleaner

ITEM NUMBER: AW-4034-0026,-0005,-0055 & 0025

DOT SHIPPING NAME:

Cleaning Compound, Liquid

DOT HAZARD CLASS AND I.D. NUMBER:

Not applicable

II. HAZARDOUS INGREDIENTS

COMPONENT	CAS NO.	%	TLV	PEL	TOXIC	HAZARD
Butoxyethanol	111-76-2**	1 to 2	25ppm	25ppm	N/A	Irritant

**SARA Title III of Section 313 of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR 372 requires reporting if otherwise use exceeds 68500 gallons per year.

III. PHYSICAL DATA

BOILING POINT: 212 F

SPECIFIC GRAVITY: 1.012

APPEARANCE & ODOR: Clear, yellow liquid, Ether odor

% VOLATILITY BY: <90

PHYSICAL FORM: Liquid

SOLUBILITY IN WATER: Complete

PH: 11.8 (Concentrate)

IV. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: None

EXTINGUISHING MEDIA: Not applicable.

SPECIAL FIRE FIGHTING PROCEDURES: Although this product is not combustible, if a fire occurs in the near vicinity, good fire-fighting practice dictates the use of self-contained breathing apparatus and other protective gear.

UNUSUAL FIRE AND

EXPLOSION HAZARDS: None.

V. HEALTH HAZARD DATA

NTP? NO IARC? NO OSHA REG? NO

CARCINOGENIC: The raw materials used in this product are not considered to be a carcinogen by ACGIH and OSHA.

EFFECTS OF Eyes: Can cause irritation, redness. Skin: Can cause irritation. Ingestion: Causes burns of gastrointestinal tract.

EXPOSURE:

EMERGENCY

EYE: Immediately flush with water for 15 minutes. GET PROMPT MEDICAL ATTENTION.

AND FIRST

SKIN: Flush with plenty of water. If irritation persists, GET MEDICAL ATTENTION.

AID

INGESTION: Do not induce vomiting. Drink large quantities of water or milk. GET MEDICAL ATTENTION.

PROCEDURES:

INHALATION: Remove to fresh air. Consult a physician if respiratory distress is not relieved by fresh air.

*NFPA Degree or Hazard: 4=Extreme; 3=High; 2=Moderate; 1=Slight; 0=Insignificant

Page 2; Product Name: **Mi-T-M Concentrated DECK & HOUSE WASH**

VI. REACTIVITY DATA

STABILITY - Unstable:

Stable: X

CONDITIONS TO AVOID: None

INCOMPATIBILITY:

(MATERIALS TO AVOID) Acids, Strong oxidizers.

HAZARDOUS

DECOMPOSITION

PRODUCTS: None.

HAZARDOUS POLYMERIZATION: Will not occur.

VII. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Small spills, flush with large amounts of water. Wear clothing and eye protection.

WASTE

DISPOSAL

METHOD: Dilute with water and adjust pH with dilute acid to a pH below 9.0 then dispose of in a manner acceptable to good waste management practice and in compliance with any applicable local, state and federal regulations.

VIII. SPECIAL PROTECTION INFORMATION

RESPIRATORY

PROTECTION: None required in normal conditions. When excessive mists are generated above TLV's, use a respirator.

VENTILATION: Normal room ventilation.

SKIN PROTECTION: Disposable vinyl/latex gloves suggested.

EYE PROTECTION: Safety glasses recommended.

PROTECTIVE

CLOTHING: Rubber boots if feet are exposed.

IX. SPECIAL PRECAUTIONS

PRECAUTIONS

TO BE TAKEN

IN HANDLING

AND STORING: Store at room temperature.

OTHER

PRECAUTIONS: KEEP OUT OF REACH OF CHILDREN.

WARNING

This product contains one or more chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

REVISED:05/01/03

Disclaimer of Liability.

As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of the material. Information contained herein is believed to be true and accurate but all statements or suggestions are made without any warranty, express or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.

Conforms to OSHA 174, Sep. 1985.