

# CAST IRON SUMP PUMPS

## APPLICATIONS

Ideal for average- to high-volume water and effluent removal in residential spaces such as basements, laundry facilities, and crawl spaces.

## FEATURES & BENEFITS

- Automatic submersible sump pumps
- 1-1/2" FNPT discharge
- Piggyback float switch
- Clog-resistant design (3/8" semi-solids handling)
- PSC motor
- 10' cord



RL-SC50T

RL-SC50V

Model	Item No.	UPC	HP	Switch	Volts	Amps	Cord Length	Gallons Per Hour at Height					Shut-Off	On/Off Levels	Min. Basin Diameter
								0'	5'	10'	15'	20'			
RL-SC33T	14942744	0 10121 14167 4	1/3	Tethered	115	4.3	10'	3350	3000	2460	1860	960	25'	On: 13" Off: 5"	18" or more
RL-SC33V	14942745	0 10121 14168 1	1/3	Vertical	115	4.3	10'	3350	3000	2460	1860	960	25'	On: 7.25" Off: 2.75"	11" or more
RL-SC50T	14942746	0 10121 14169 8	1/2	Tethered	115	5.3	10'	4300	3840	3000	2220	1440	28'	On: 13" Off: 5"	18" or more
RL-SC50V	14942747	0 10121 14170 4	1/2	Vertical	115	5.3	10'	4300	3840	3000	2220	1440	28'	On: 7.25" Off: 2.75"	11" or more

## CARTON SPECIFICATIONS

Model	Length	Width	Height	Weight (lbs)	Carton Cubes (cu ft)	Pallet Quantity	Quantity per Layer	Layers per Pallet
RL-SC33T	7.25"	8.75"	13"	20	0.48	81	27	3
RL-SC33V	6.75"	8.75"	13"	21	0.44	81	27	3
RL-SC50T	7.25"	8.75"	13"	20	0.48	75	25	3
RL-SC50V	6.75"	8.75"	13"	21	0.44	75	25	3

### Cast Iron Sump Pumps

