

EcoLift SERIES

NON-POWERED VERTICAL LIFTS



Performance

	EcoLift 50	EcoLift 70
Working Height	10 ft 11 in. (3.33 m)	13 ft 2.5 in (4.03 m)
Platform Height	4 ft 11 in. (1.50 m)	7 ft 2.5 in (2.20 m)
Stowed Height	5 ft 1 in. (1.55 m)	6 ft 4 in. (1.94 m)
Stowed Width	27.5 in. (0.7 m)	27.5 in. (0.7 m)
Stowed Length	3 ft 2.7 in. (0.985 m)	4 ft 2.3 in. (1.28 m)
Platform Size	28 x 23.6 in. (72 x 60 cm)	33.4 x 25.4 in. (85 x 64.4 cm)
Rated Capacity	330 lb (150 kg)	330 lb (150 kg)
Weight	397 lb (180 kg)	672 lb (305 kg)

Standard Features

- Unlimited Lift Cycles
- Rust-Free Aluminum Platform w/ Diamond Tread
- Full-Height Self-Closing Saloon Gate
- Tool Tray
- Frame-Mounted Bubble Level
- Protective Wall Bumpers
- Integrated Fork Pockets
- Auto-Braked When Entering Platform
- "Auto-lok" Brake on Elevation
- Mechanically Detented Handle

Applications

- Commercial and Residential Painting
- Facility Maintenance
- Displays and Decorating
- HVAC Maintenance
- Renovations and Remodeling
- Plant Maintenance
- Equipment Maintenance Installers — Cable, Security, Professional



EcoLifts are an Eco-friendly alternative to your powered access needs. They are hydraulic oil and battery free. And with no need to charge, **EcoLifts** have no energy consumption.

The JLG "1 & 5" Warranty

JLG Industries, Inc. backs its products with its exclusive "1 & 5" Warranty. We provide coverage on all products for one (1) full year, and cover all specified major structural components for five (5) years. Due to continuous product improvements, we reserve the right to make specification and/or equipment changes without prior notification. This machine meets or exceeds applicable OSHA Regulations in 29 CFR 1910.67, 29 CFR 1926.453, ANSI A92.3-2006, and CSA Standard CSA B354.4, as originally manufactured for intended applications.

Part No.: 3132134
R051601
Printed in USA



JLG Industries, Inc.

1 JLG Drive
McConnellsburg, PA 17233-9533
Telephone 717-485-5161
Toll-free in US 877-JLG-LIFT
Fax 717-485-6417
www.jlg.com

An Oshkosh Corporation Company