



Micro19-XD™ **Xtra Deck®** **Micro Scissor**

Patent Pending

- Pull-Down Xtra Deck® Gives Additional 20 in. (51cm) Height for 1 Person
- 22 in. (56cm) Width Allows Access Through Ceiling Panels
- Guardrails on 3 Sides Slide Up to Meet Regulation Height with a 4th Side Swinging Gate Rail Enabling Both Hands to Freely Complete Work Tasks
- Deploys or Stows in Seconds
- Can be Used with the Roll-Out Deck Extended or Retracted

**Xtra Deck® is There When You Need It
and Folds Up When You Don't!**



Standard Features

Work Area

Roll-Out Deck Extension with Incremental Locking Positions
Standard Full Height Swing Gate
Lanyard Attachments (2)
Xtra Deck® Additional 20-Inch Height Platform (*Patent Pending*)

Performance

Direct Electric Drive
Fully Proportional Drive and Lift Controls

Power

24v 115Ah AGM Batteries
Battery Charge Indicator

Serviceability

Lubrication-Free Scissor Bearings
Easy Maintenance Access to Mechanical and Electrical Components in a Slide-Out Tray
Parking Brake Override Feature

Safety

Xtra Deck® Additional 20-Inch Height Platform Provides a Safer Solution to Standing on Mid Rails (*Patent Pending*)
Platform Overload Detection
Dedicated Compartment Protects Electrical and Hydraulic Components
Emergency Shut-Off at Platform and Lower Controls
Non-Skid Metal Deck Construction
Descent Alarm
Drive Speed Interlock
Multi-Axis Tilt Sensor
Scissor Maintenance Lock
Multiple Disc Brakes

Other Features

Removable Upper Controls
Voltage-Compensating Fully Automatic Battery Charger
Hour Meter
Machine Tie Downs
Non-Marking Tires
All Motion Alarm
Fork Lift Pockets
Flashing Beacon (Continuous)

Optional Features

Proactive Platform Safety System® (PPSS)

Leak Containment System® (LCS)
Patent Pending
900W Inverter



MEC Aerial Work Platforms

Tel: 559.842.1500 | 1401 S. Madera Avenue, Kerman, CA 93630 | USA

Toll free: 1.877.MEC LIFT | 1.877.632.5438 | Fax: 559.842.1520

Email: info@MECawp.com | www.MECawp.com

MEC®, Proactive Platform Safety System®, Xtra Deck®, and Leak Containment System® are registered trademarks and Micro19-XD™ is a trademark of California Manufacturing & Engineering Co., LLC.
Xtra Deck® and Leak Containment System® are Patent Pending. 97030 DTD 0720

Micro19-XD™	U.S.	Metric
Heights		
Indoor Working Height*	24 ft. 4 in.	7.6 m
Outdoor Working Height*	20 ft. 9 in.	6.5 m
Indoor Platform Height	18 ft. 4 in.	5.6 m
Outdoor Platform Height	13 ft.	4 m
Xtra Deck® Height	20 in.	50 cm
Stowed Height (Top Guardrail)	83.5 in.	2.12 m
Stowed Height (Rails Folded)	79 in.	2 m
Stowed Height (Platform Floor)	39 in.	1 m
Guardrail Height	43.3 in.	1.1 m
Toeboard Height	6 in.	15 cm
Ground Clearance (Stowed)	2.5 in.	6 cm
Ground Clearance (Elevated)	0.6 in.	1.5 cm
Dimensions		
Length-Stowed (Overall)	60 in.	1.5 m
Length-Stowed (Ladder Removed)	54 in.	1.3 m
Chassis Width	32 in.	76 cm
Platform Length (Extended)	78 in.	1.9 m
Platform Length (Retracted)	54 in.	1.3 m
Roll-Out Deck Length	24 in.	60 cm
Platform Width (Outside)	27.5 in.	70 cm
Xtra Deck® Width	22 in.	56 cm
Wheelbase	45 in.	1.15 m
Total Lift Capacity	500 lbs.	227 kg
Personnel Capacity - 1 Person	Indoor/Outdoor: 18.4 ft./13 ft. 5.6m/4m	
Roll-Out Deck Capacity	250 lbs.	113 kg
Xtra Deck® Capacity - 1 Person	250 lbs.	113 kg
Speed		
Raise/Lower Speed	26 s / 20 s	
Drive Speed (Stowed)	2.5 mph	4 km/h
Drive Speed (Elevated)	0.5 mph	.8 km/h
Performance		
Gradeability	25%	
Turning Radius (Inside)	18 in.	.45 m
Weight**	2,820 lbs.	1,280 kg
Power Source	24v 115Ah AGM Batteries	
Controls	Proportional drive & lift controls	
Tires	9 in.	23 cm

*Metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft. to platform height.

**Weight may vary with certain options or configurations.

Important - MEC scissor lifts must be on a hard level surface while elevated.

Warranty - MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. This warranty applies to the original owner only. Consult your MEC dealer for warranty details.

Meets or exceeds the requirements of ANSI A92.20 and CSA B354.6

Specifications subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.

Distributed by: