



MODEL D2002HPV5

ROLAIR® STANDARD FEATURES

- PUMP:** ROLAIR® Quality, Heavy Duty, Single Stage, Ball Bearings, Cast-Iron Cylinder, Metal Filter/Silencer with Replaceable Filter Element, Stainless-Steel Reed Valves and Splash Lubrication Ensure Longer Life.
- MOTOR:** 2 HP, 3400 RPM, S-1 Rated for Continuous Duty, Low-Amp Draw, Overload Protection with Manual Reset, 115 Volt, 60 Hz, Heavy-Duty/Industrial-Grade with Ball Bearings for Greater Durability.

SPECIFICATIONS

MODEL	MOTOR HP	# OF CYLS	CU. FT. DISPLACED	CU. FT. DELIVERED @ 90 PSI	TANK CAP. (GAL.)	DIMENSIONS (L X W X H) (INCHES)	APPROX. SHIPPING WT. (LB.)
D2002HPV5	2	1	8.7	4.1	4.5	18 X 16 X 17	62

STANDARD EQUIPMENT

- "Square D" Pressure Switch with On/Off Lever
- Air Line Regulator and Pressure Gauge
- Universal Quick-Disconnect with Plug
- 110/135 PSI Operating Pressure
- Factory Tested
- 14.2 Amp Motor
- Safety Relief Valve
- 12 oz. Crankcase Pre-Filled with Oil