

50-310 Benchtop Oscillating Belt/Spindle Sander



MOTOR

Horsepower	1/2 HP
Amps	4.3
Volts, Hz	110V, 60 Hz
Speed (No Load)	2,000 RPM

BELT/SPINDLE SANDER

Table	12-5/8" x 12"
Sanding Belt	4" x 24"
Spindle Length	4-1/2"
Spindle Diameters (5)	1/2", 3/4", 1", 1-1/2", 2"
Dust Outlet	1-1/2" O.D or 1-5/16" ID

OVERALL

Height	18-1/4"
Width	17"
Depth	18"
Base Size	16" x 18-1/4"
Net Weight	27.5 lbs.
Shipping Weight	31 lbs.
Shipping Carton	21" x 18" x 19" (L x W x H)

WARRANTY 5 YEARS

ACCESSORIES

MODEL	DESCRIPTION
50-45060	60 Grit Sanding Sleeves Diameters 1/2", 3/4", 1", 1-1/2", 2" (PK 5)
50-45100	100 Grit Sanding Sleeves Diameters 1/2", 3/4", 1", 1-1/2", 2" (PK 5)
50-45150	150 Grit Sanding Sleeves Diameters 1/2", 3/4", 1", 1-1/2", 2" (PK 5)
50-45303	Assorted 3" Sanding Sleeves Grits: 60/100/150 (PK 3)

Oscillating Belt/Spindle Sander Model 50-310 is a specialized sander for the fast and accurate sanding of curved board edges. The 4" x 24" belt and spindle sanding sleeves oscillate up-and-down 5/8", 58 time per minute while the spindle spins, providing more efficient abrasive cutting action. Powerful 1/2 HP motor, ample cast metal table and 5 spindle diameters (1/2" to 2") with 6 table inserts make this a valuable machine for every shop. Includes 4-1/2" long 80 grit abrasives.



LARGE 16" X 15-7/8" WORK SURFACE



TABLE TILT 0-45°



INCLUDES 1-1/2" DUST PORT



ONBOARD STORAGE

To find a dealer or products questions call (877) 884-5167 or visit RIKONTOOLS.COM