



ROLAIR® STANDARD FEATURES

PUMP: ROLAIR® Quality, Heavy Duty, Single Stage, Ball Bearings, Cast-Iron Twin-Cylinders, Hardened-Steel Valve Plates with Swedish Lamellar Reed Valves, Aluminum-Alloy Connecting Rods with Automotive-Style Inserts, Multi-Finned 11" Flywheel, Oil Sight Gauge and Splash Lubrication.

MOTOR: 1.5 HP 1755 RPM Open Drip-Proof
115/230 Volt, 60 Hz Ball Bearings
Overload Protected with Manual Reset
S-1 Rated for Continuous Duty

TANK ASSEMBLY: Non-Code, 20 Gallons

WHEELS: Two 410/350 x 4 Flat-Free Tires

PERFORMANCE @ 90 PSI:

Cu. Ft. Displaced - 10.1
Cu. Ft. Delivered - 7.3

DIMENSIONS:

L42" x W22" x H34"

APPROXIMATE SHIPPING WEIGHT:

198 lb.

STANDARD EQUIPMENT

- Industrial "Square D" Pressure Switch with Relief Valve
- Intake Filter with Silencer and Replaceable Element
- Universal Quick-Disconnect Fitting
- Totally Enclosed Steel Belt Guard
- 12-3 Cord with Dead Front Plug
- Accessory Support Bracket
- Pressure Gauge 0-200 in 5 lb. Graduations
- 110/135 PSI Operating Pressure
- On/Off Lever
- Safety Relief Valve

OPTIONAL EQUIPMENT

Constant-Speed Operation, Dual-Control Operation, Dual-Voltage Switch,
Filter-Regulator-Lubricator Sets, Fully-Pneumatic Tires, ASME Tank