



* Shown w	optiona /	l Aluminum	Wheels
-----------	-----------	------------	--------

WIDTH/ LENGTH	WEIGHT	BASE PRODUCT CODE	MSRP
*5X8	547#	5X8ODSA22	
6X10	660#	6X100DSA30	
6X12	740#	6X12ODSA30	
7X12	780#	7X120DSA30	
7X14	880#	7X140DSA30	

^{*} Standard with 2,200# Axle & ST185/80R13 Tires (GVWR 2,200#)

HIGHLIGHTS

- Perimeter Tube Frame
- 3" x 6" Extruded Alum. Triple Tongue Design
- ATP Fenders w/ Gussets
- Surface Mount L.E.D. Lighting
- Pressure Treated Prime Decking
- Fold-In Radius Gate
- Stake Pockets
- 2" x 4" Tube Rear Gate Supports

	STANDARD FEATURES			POPULAR OPTION	IS —		
STRUCTURAL			MSRP		MSRP		MSRP
Cross Members	2" x 3" Tube 24" OC	16" OC		12" OC			
Frame	2" x 3" Perimeter Tube (5' & 6' Wide) 2" x 4" Perimeter Tube (7' Wide)						
Jack	2,000# Top-Wind Set Back Jack w/ Foot	Ultimate Adj. 2K Jack w/Foot		5,000# Jack w/ Foot	:	Caster Wheel ILO Foot	
Rear Loading	48" Fold-In Radius Tube Gate	48" Bi-Fold Square Gate ILO Strai	ght	60" Bi-Fold Square Gate ILO Straight			
Sides	1.5" x 1.5" Tube 14" Tall	24" Sides ILO 14"		14" ATP Skirting .045		24" ATP Skirting .045	
Side Loading	Optional	53" Radius Side Gate		53" Bi-Fold Square Gate			
Tongue	3" x 6" Extruded Alum. Triple Tongue						
Top Rail	2" x 2" Tube						
RUNNING GEAR							
Axles	3,500# E-Z Lube 4" Drop Spring 1 Idler	Add Brake		Torsion Axle (Idler)		Torsion Brake Axle	
Tires/ Wheels	ST205/75R14 Nitrogen Filled Silver Mod Steel		lum- iteel-	Spare Mount		Aluminum Wheels Upgrade	
FLOORS							
Floor	Dura Color Prime Dimensional Pine	Extruded Aluminum					
COMPONENTS					:		
Coupler	2" Straight	2 ^{5/16} " Straight		Adjustable Coupler			i
Stake Pockets	Included	Additional Stake Pockets					
Tie Downs	Optional	1,000# D-Rings (Installed)		5,000# D-Rings (Installed)			