



Hot Electric Series



SPECIFICATIONS

Oil Fired Portable Pressure Washer

GENERAL				ELECTRICAL				BURNER			DIMENSIONS/LBS.			
Model	GPM	PSI	HP	Drive	Volt	AMP	Ph.	Max. Temp.	Tank Size Gal.	BTU	L	W	H	LBS.
HSEPW-1500	2.0	1500	2	Direct	115/120	20	1	250°F	7.4	170,000	32"	25"	41.75"	208
HSEPW-2700	2.5	2700	5	Direct	220/230	20	1	250°F	7.4	275,000	32"	25"	41.75"	225

FEATURES:

- Stainless Steel Heating Chamber Wrapper
- Heavy Duty 12 Ga. Welded Frame
- Direct Drive Industrial Triplex Pump
- Molded Poly Fuel Tank
- Pressure Relief Valve
- Exclusive 1/2" Sch. 80 Steel Coil Design
- Bucket Insulation System
- High Efficiency Burner
- Durable Powdercoated Frame & Components
- Indicator Lights

- Adjustable Temp. Control
- Stainless Steel Nozzles (0°, 15°, 25°, 40°)
- Soap Nozzle
- 10" Flat Free Tires/Mag Style Wheels
- Panel Mounted Controls
- Trigger Gun/Wand Holder
- 50' 3/8" High Pressure Hose
- 36" Gun/Lance Assembly w/Quick Coupled Nozzles
- Heavy Duty Electric Motor
- 36' GFCI Power Cord
- Wet Steam Nozzle

LIMITED WARRANTY:

1 YR
1 YR
1 YR
1 YR
2 YR

Craftsmanship
Motor
Burner
Pump
Coil

A Closer Look at the Features:



Notes:

Configured for you by

